



---

# Industrial drilling machine

## Description

---

Low-noise column drill of German top quality with very high accuracy. Equipped with variable speed with digital speed readout. This UNIMAX 2S by Maxon is characterised by its high quality, made possible by the knowledge and experience of the German manufacturer. The UNIMAX 2S has a 20 mm drilling capacity. In addition, this V-belt driven drill has a wide speed range adjustable with potentiometer, which makes drilling in various types of material no problem. The table is height-adjustable and/or rotatable. Despite its powerful engine, this machine is equipped with a 230V connection, making this drill suitable for every workshop! The UNIMAX 2S is standard equipped with a left/right spindle movement and is also available in a table version and/or with TAP device.

### Properties:

- Drilling capacity: 20 mm
- Wide range of application
- Speed adjustment via potentiometer
- German top quality
- Very high accuracy



## Extra information

|                       |                                  |                      |
|-----------------------|----------------------------------|----------------------|
| Item number           | MX44668                          |                      |
| Model                 | UNIMAX 2S                        |                      |
| EAN                   | 8718242157025                    |                      |
| CBS Statistics number | 84596990                         |                      |
| Article group         | Industrial drilling machine      |                      |
| Brand                 | MAXION                           |                      |
| Features              | Drilling capacity                | 20 mm                |
|                       | Tap capacity                     | M 12                 |
|                       | Distance spindle – column        | 225 mm               |
|                       | Spindle taper                    | MT 2                 |
|                       | Engine power                     | 1,5 kW               |
|                       | Voltage                          | 230 V                |
|                       | Drilling depth                   | 100 mm               |
|                       | Maximum distance spindle – table | 55 – 880 mm          |
|                       | Table dimensions                 | 450 x 315 mm         |
|                       | T slots                          | M16                  |
|                       | Column diameter                  | 90 mm                |
|                       | Speed range                      | 100 – 4000 omw/min   |
|                       | Variable speed                   | Ja                   |
|                       | Drive                            | V-snaar              |
|                       | Weight                           | 170 kg               |
|                       | Height                           | 1745 mm              |
|                       | Packaging dimensions             | 2200 x 740 x 1250 mm |
|                       |                                  |                      |
| Article group code    | 1027247                          |                      |

Product images



