



---

# Ceramic spray

## Description

---

High-quality ceramic mounting spray consisting of small ceramic particles with excellent lubricating qualities. This spray is completely free of metal and reduces wear in places where there is much friction. Strong adhesive and extremely resistant to high pressure. Particularly suitable for threaded connections which are exposed to high temperature and corrosive influences. Allows quick and easy disassembly even if they are exposed to temperatures up to + 1200 ° c, to corrosion or heavy pressure. By using the spray corrosion can be avoided. Widely used for the assembly and disassembly of threaded connections, brake parts (ABS braking system), manifolds, flanges, fittings, the lubrication of brake pads, exhaust systems, wheel nuts, machine parts, etc. Suitable for e.g. greasing bolts and nuts during the final assembly.

### Properties:

Free of metal

Protects against corrosion, wear, burn, etc.

Fixes strongly

Water-acid and salt-resistant

Temperature range -40 ° c to + 1200 ° c

Simplifies the assembly and disassembly of threaded connections such as spark plugs, exhaust pipes, flanges etc.

Offers optimal protection against corrosion

## Extra information

---

Item number	21121024	
Model	JT 2000 N	
Model group	JT ...	
EAN	8718242131803	
CBS Statistics number	84671110	
Article group	TCE Machines, Lubricants & Accessories	
Brand	TCE	
Features	Max. temp.	2000 °C
	Volume	400 ml
	Gross volume	500 ml
Article group code	944067	

## Product images

---



