



Professional bench drilling machine 20 mm - 230V

Description

The HU 20-2 NG Topline is a very comprehensive table drilling machine for the professional user. This 20 mm V-belt driven table drilling machine is fully equipped according to the latest CE standards. The user is therefore assured of pleasant and safe use. Are you looking for an accurate table drill with a large capacity? Then a 20 mm table drill is the perfect solution!

The HU 20-2 NG Topline is equipped with a work light to better illuminate your workpiece, an easily adjustable drilling depth and an easily adjustable work table. The work table can be turned both horizontally and vertically and can be swivelled around the column. The table has a cross of the t-slots, which makes it possible to use almost all clamps! With the motor's tensioning lever, you can easily release the V-belts from their tension, allowing you to quickly replace or reposition them. With the wide speed range of the V-belts, you can easily drill into various materials with corresponding drill diameters up to 20 mm. With the included quick-release drill head, you can easily clamp drills up to 16 mm, and you can also easily clamp drills with a MK2 holder directly in this drill. Finally, this machine is of course equipped with an emergency stop and protective covers.

Features:

- Professional quality
- V-belt driven
- CE compliant
- Including protective cover
- Including emergency stop
- Including drill head
- Inclusive drill bit
- Including drive spigot
- Including working light
- With adjustable drilling depth
- Flexible work table

Extra information

| | |
|-----------------------|------------------------|
| Item number | 11253 |
| Model | HU 20-2 NG Topline |
| EAN | 8718242559362 |
| CBS Statistics number | 84592900 |
| Article group | HUVEMA Machines Retail |
| Brand | Huvema |

Features

| | |
|----------------------------------|---------------------|
| Drilling capacity | 20 mm |
| Distance spindle - column | 215 mm |
| Spindle taper | MT 2 |
| Engine power | 1,1 kW |
| Voltage | 230 V |
| Drilling depth | 80 mm |
| Maximum distance spindle - table | 350 mm |
| Maximum distance spindle - foot | 600 mm |
| Table dimensions | 356 x 356 mm |
| T slots | 4x M14 |
| Column diameter | 80 mm |
| Speed range | 160-3000 rpm |
| Number of revs | 16 |
| Variable speed | No |
| Drive | V-belt |
| Weight | 58 kg |
| Machine dimensions | 650 x 320 x 1030 mm |
| Packaging dimensions | 1390 x 540 x 240 mm |

Article group code

1960674

Product images



