



Professional column drilling machine 20 mm - 230V

Description

The HU 20K-2 NG Topline is a very comprehensive column drilling machine for the professional user. This 20 mm V-belt driven column drill is fully equipped according to the latest CE standards. The user is therefore assured of pleasant and safe use. Are you looking for an accurate column drill with a large capacity? Then a 20 mm table drilling machine is a great solution!

The HU 20K-2 NG Topline column drill is equipped with, among other things, a work light for better illumination of the workpiece, an easily adjustable drilling depth and a work table that is easy to adjust. The work table can be rotated both horizontally and vertically and swivels around the column. The table has a cross of the t-slots, which makes it possible to use almost all clamps! With the motor's tensioning lever, you can easily release the V-belts from their tension, allowing you to quickly replace or reposition them. With the wide speed range of the V-belts, you can easily drill into various materials with corresponding drill diameters up to 20 mm. With the included quick-release drill head, you can easily clamp drills up to 16 mm, and you can also easily clamp drills with a MK2 holder directly in this drill.

Finally, this machine is of course equipped with an emergency stop and protective covers.

Features:

- Professional quality
- V-belt driven
- CE compliant
- Including protective cover
- Including emergency stop
- Including drill head
- Inclusive drill bit
- Including drive spigot
- Including working light
- With adjustable drilling depth
- Flexible work table

Extra information

Item number	11255
Model	HU 20K-2 NG Topline
EAN	8718242559409
CBS Statistics number	84592900
Article group	HUVEMA Machines Retail
Brand	Huvema

Features	Drilling capacity	20 mm
	Distance spindle - column	215 mm
	Spindle taper	MT 2
	Engine power	1,1 kW
	Voltage	230 V
	Drilling depth	80 mm
	Maximum distance spindle - table	590 mm
	Maximum distance spindle - foot	1100 mm
	Table dimensions	356 x 356 mm
	T slots	4x M14
	Column diameter	80 mm
	Speed range	160-3000 rpm
	Number of revs	16
	Variable speed	No
	Drive	V-belt
	Foot dimensions	505 x 345 mm
	Weight	81 kg
	Machine dimensions	720 x 330 x 1620 mm
Packaging dimensions	1410 x 540 x 250 mm	

Article group code 1960678

Product images



