

Huvema B.V Kennedylaan 14 5466 AA Veghel Nederland info@huvema.nl Tel +31 413 34 22 75 KVK 16028008 Btw NL003107905B01



Professional bench drilling machine - 400V

Description

he HU 16-4 NG Topline is a very extensively equipped table drilling machine for the professional user in POWER CURRENT VERSION. This 16 mm V-belt driven table drilling machine is fully equipped according to the latest CE standards.

The user is thus assured of pleasant and safe use. Are you looking for an accurate drilling machine, easy to use and yet with a wide range of possibilities? Then look no further!

The HU 16-4 NG Topline is equipped with a work light to better illuminate your workpiece, an easily adjustable drilling depth and an easily adjustable work table. The work table can be turned both horizontally and vertically and can also be rotated around the column. The table has a cross of t-slots, so that almost all clamps can be used! With the motor's tensioning lever, you can easily release the V-belts from their tension so that they can be quickly replaced or moved. With the large speed range of the V-belts, you can easily drill in various materials with corresponding drill diameters up to 16 mm. Finally, this machine is of course equipped with an emergency stop and protective covers. Features:

- Professional quality
- V-belt driven
- CE-compliant
- Including protective cap
- Including emergency stop
- Including drill head
- Including drill bit
- Including drive spigot
- Including work light
- · With adjustable drilling depth
- Flexible work table
- Power current version

Extra information

| Item number | 11252 |
|-----------------------|------------------------|
| Model | HU 16-4 NG Topline |
| EAN | 8718242559355 |
| CBS Statistics number | 84592900 |
| Article group | HUVEMA Machines Retail |
| Brand | Huvema |

| Features | Drilling capacity | 16 mm |
|--------------------|-------------------------------------|------------------------|
| | Distance spindle - column | 190 mm |
| | Spindle taper | MT 2 |
| | Engine power | 0,6 kW |
| | Voltage | 400 V |
| | Drilling depth | 80 mm |
| | Maximum distance spindle - table | 350 mm |
| | Maximum distance spindle - foot | 600 mm |
| | Table dimensions | 305 x 305 mm |
| | T slots | 4x M14 |
| | Column diameter | 73 mm |
| | Speed range | 180-2740 rpm |
| | Number of revs | 12 |
| | Variable speed | No |
| | Drive | V-belt |
| | Weight | 58 kg |
| | Machine dimensions | 650 x 320 x 1030 mm |
| | Packaging dimensions | 890 x 500 x 300 mm |
| Article group code | 1700674 | |

Product images





















