



Professional bench drilling machine 16 mm – 230V

Description

The HU 16-2 NG Topline is a very comprehensive table drilling machine for the professional user. This 16 mm V-belt driven table drilling machine is fully equipped according to the latest CE standards. This assures the user of pleasant and safe use. Are you looking for an accurate drilling machine that is easy to use and yet has a wide range of possibilities? Then look no further!

The HU 16 NG-2 Topline is equipped with a work light to better illuminate your workpiece, an easily adjustable drilling depth and an easily adjustable work table. The work table can be turned both horizontally and vertically and can also be swivelled around the column. The table has a cross of the t-slots, which makes it possible to use almost all clamps! With the motor's tensioning lever, you can easily release the V-belts from their tension, allowing you to quickly replace or reposition them. With the wide speed range of the V-belts, you can easily drill into various materials with corresponding drill diameters up to 16 mm. Finally, this machine is of course equipped with an emergency stop and protective caps.

Features:

- Professional quality
- V-belt driven
- Meets CE standards
- Including protective cap
- Including emergency stop
- Including drill head
- Inclusive drill bit
- Including drive spigot
- Including working light
- With adjustable drilling depth
- Flexible work table

Extra information

Item number	11250
Model	HU 16-2 NG Topline
EAN	8718242559416
CBS Statistics number	84592900
Article group	HUVEMA Machines Retail
Brand	Huvema

Features	Drilling capacity	16 mm
	Distance spindle – column	190 mm
	Spindle taper	MT 2
	Engine power	0,6 kW
	Voltage	230 V
	Drilling depth	80 mm
	Maximum distance spindle – table	350 mm
	Maximum distance spindle – foot	600 mm
	Table dimensions	305 x 305 mm
	T slots	4x M14
	Column diameter	73 mm
	Speed range	180-2740 rpm
	Number of revs	12
	Variable speed	No
	Drive	V-belt
	Weight	58 kg
	Machine dimensions	650 x 320 x 1030 mm
	Packaging dimensions	890 x 500 x 300 mm
Article group code		1960677

Product images



