



Teach in ProtoTRAK CNC lathe

Description

Capacity and added value. After your first day, you'll wonder why you ever kept using a conventional lathe.

The Prototrak CNC is the most user-friendly control for single pieces and small series jobs. Program at lightning speed without knowing a single code. No loss of flexibility compared to a conventional machine. Reduce your labour costs 4 to 10 times, every time, and always.

No surprises in the options, that's why it's all included as standard included:

Free 1 day training for up to 3 people. You do not need to know anything about CNC, only the basis of conventional machining is sufficient.

Free positioning according to DIN8606

Self-centering 3 chuck

Freezer pump installation

Quick change chisel holder with 6 holders

Loose head

Constant cutting speed

Fully automatic lubrication

Slide guard and solid back wall

Fixed centres and reducer bush

Lightening

TRAKing[®]

Options

Automatic 4-Road chisel holder

Surface plate, independent 4 claw, fixed and/or carriage glasses

Off-line software

Sophisticated options

Transport of the machine and placement on the workstation.

DXF Converter

Chisels

Extra information

| | | |
|-----------------------|--|-------------------------|
| Item number | XD16831 | |
| Model | RLX 1630x760 | |
| EAN | 8718242478328 | |
| CBS Statistics number | 84581900 | |
| Article group | CNC | |
| Brand | XYZ | |
| Features | Swing over bed | 400 mm |
| | Distance between centres | 760 mm |
| | Hole through spindle | 54 mm |
| | Engine power | 5,75 kW |
| | Maximum turning diameter above the trolley | 218 mm |
| | Cross slide travel | 216 mm |
| | Maximum cutting length | 760 mm |
| | Spindle nose | D 1-6 camlock |
| | Uptake of the fixed head | MT4 |
| | Speed range | 150-2500 rpm (variable) |
| | Movement tail stock taper | 127 mm |
| | Tail stock taper | MT4 |
| | Tail stock taper | 60 mm |
| | Width of bed | 320 mm |
| | Main dimensions LxWxH | 2080 x 1000 x 1800 mm |
| Weight | 1750 kg | |
| Voltage | 400 V | |
| Article group code | 1282436 | |

Product images

