

Huvema B.V Kennedylaan 14 5466 AA Veghel Nederland info@huvema.nl Tel +31 413 34 22 75 KVK 16028008 Btw NL003107905B01



ProtoTRAK CNC lathe

Description

104 mm diameter and 1000 mm between centres. The protoTRAK control makes this machine a real winner.

The Prototrak CNC is the most user-friendly control for single pieces and small series jobs.

Right-speed programming without knowing a single code.

No loss of flexibility compared to a conventional machine.

Reduce your labor costs 4 to 10 times, every time, and always.

No surprises in the options, that's why this is all included as standard included: Free I day training for up to 3 people. You don't need to know anything about CNC, only the basis of conventional machining is sufficient. Free positioning according to DIN8606 Selfcentric 3 chuck Cooling pump installation Quick change chisel holder with 6 holders Loose head Constant cutting speed Lubrication with joystick Fully automatic Slubrication Slide guard and solid rear wall Fixed centres and reducer bush Lighting TRAKing®

Extra information

Item number	XD16835RLX
Model	RLX 555x1000
EAN	8718242478366
CBS Statistics number	84581900
Article group	CNC
Brand	XYZ

Swing over bed	
0	560 mm
Distance between centres	1000 mm
Hole through spindle	104 mm
Engine power	11 kW
Maximum rotation diameter in the bag	780 mm
Maximum turning diameter above the trolley	350 mm
Cross slide travel	280 mm
Maximum cutting length	900 mm
Spindle nose	D 1-11 camlock
Uptake of the fixed head	MT7 in reducer
Speed range	30-1800 rpm (vario in 2 stages)
Movement tail stock taper	160 mm
Tail stock taper	
Tull stock tupel	MT5
Tail stock taper	MT5 90 mm
Tail stock taper	90 mm
Tail stock taper Width of bed	90 mm 370 mm 2600 x 1600 x 1950
Tail stock taper Width of bed Main dimensions LxWxH	90 mm 370 mm 2600 x 1600 x 1950 mm
	 Hole through spindle Engine power Maximum rotation diameter in the bag Maximum turning diameter above the trolley Cross slide travel Maximum cutting length Spindle nose Uptake of the fixed head Speed range Movement tail stock taper

Product images







