

Huvema B.V Kennedylaan 14 5466 AA Veghel Nederland info@huvema.nl Tel +31 413 34 22 75 KVK 16028008 Btw NL003107905B01



# Rubber swivel castor with brake Ø100mm with mounting plate

### Description

Robust swivel castor with brake function. The wheel has a rubber running surface and an outer diameter of 100 mm. This braked swivel castor has double brakes, which means that once the wheel is on the brake, the wheel and the direction of rotation are simultaneously blocked. The wheel is fitted with a mounting plate, which allows easy attachment of the wheel with 4 bolts. The very solid steel base offers an excellent load capacity of 70 kilograms, The castor can rotate 360 degrees and has relatively good rolling properties on less flat surfaces. Compared to a nylon wheel, this rubber wheel runs more quietly and wears less. Thanks to the hub with roller bearing, this wheel runs smoothly and shock-free.

#### Features:

- Roller-bearing hub
- Economically priced
- Load capacity per wheel : 70 kg.
- Plate bore Ø 9 mm
- Plate L x W : 100x80 mm
- Resistant to oxidation
- Housing made of high-grade galvanised steel
- Construction height: 127 mm
- Suitable for temperatures from -20°C to +80°C.

### **Extra information**

Item number	V1500222
Model	1500222
EAN	8004878649509
Article group	HUVEMA Webshop Machines & Apparatuur
	Valex
Brand	valex
Features	Diameter wheel 100 mm
Article group code	2163425

## **Product images**







