

Huvema B.V Kennedylaan 14 5466 AA Veghel Nederland info@huvema.nl Tel +31 413 34 22 75 KVK 16028008 Btw NL003107905B01



Industrial drilling machine

Description

Industrial column drill of European manufacture, with precise and silent operation. The drill is variable in speed adjustable via v-belt transmission with potentiometer (art. 11159). Speed can be accurately adjusted in various steps with (within these steps) stepless adjustment. Equipped with a precision spindle with hardened morse taper. The drilling table is adjustable in height by means of a swivel arm, in addition there is the possibility to turn the table away. The table dimensions are 350 x 250 mm. The table is equipped with T slots. The drill is built according to the highest safety standards. Thanks to its variable speed, this drill can be widely used on different types of material.

Art. 11159: with potentiometer for variable speed.

Characteristics:
Variable speed control
Manual feeding
V-belt transmission
Electronic potentiometer (art. 11159)
Adjustable drilling table
Protective cover with microswitch

Extra information

Item number	11161	
Model	HU 25 PG-4	
EAN	8718242197205	
CBS Statistics number	84592900	
Article group	V-belt drills	
Brand	Huvema	
	Drilling capacity	25 mm
Features	Tap capacity	M 16
	Distance spindle - column	203 mm
	Spindle taper	MT 3
	Engine power	0,75 kW
	Voltage	400 V
	Drilling depth	100 mm
	Column diameter	98 mm
	Transmittance	Stepped pulley
	Speed	12 (164 - 2460) rpm
	T-slot dimensions and interaxis	N° 2 / 12 / 100 mm
	T-slot sizes and interaxis for cross table	N° 2 / 16 / 60 mm
	Dimension of working table	350 x 250 mm
	Worktable	Tilting table with rack
	Dimensions	1650 x 500 x 850 mm
	Weight	185 kg
Article group code	1689128	

Product images









