Huvema B.V
Kennedylaan 14
5466 AA Veghel
Nederland

info@huvema.nl
Tel +31 413 34 22 75
KVK 16028008
Btw NL003107905B01

Tapping machine M3~M12

Description

This pneumatic tapping arm, type AT-12/II mm has a working range of up to 1900 mm. The tapping capacity of this machine is M3-M12. Thanks to its construction, the arm can be quickly and easily positioned near the workpiece. Easy to mount on a worktop.

This tapping arm can be used to produce internal threads of various sizes. The design of the movable arm offers you an easy and convenient way to operate. Depending on the working conditions, you can also purchase accessories for multi-functional tapping.

Features:

- Supplied with reducing/lubricating set as standard
- Working range between 200 mm and 1900 mm
- For tapping M3-M12
- Pneumatic tapping spindle included
- With air unit and air hose
- For professional and industrial use.
- Optional: adapter B16 (art. no. 31690)
- Optional: work table (art. no. 31779)

Including 6 tapping jars with slip clutch
M3 20111812 DIN 371 19/1
M4 20111814 DIN 371 19/1
M6 20111816 DIN 371 19/1
M8 20111817 DIN 371 19/1
M10 20111818 DIN 376 19/1
M12 20111820 DIN 376 19/1

Extra information

Item number	31681	
Model	HU Tap AT-12/II M3-M12	
EAN	8718242076296	
CBS Statistics number	84597000	
Article group	HUVEMA Machinery Industry	
Brand	Huvema	
Features	Tap capacity	M3~M12
	Speed	400 rpm
	Working length	200 - 1900 mm
	Taps	6 taps with slipping clutch M3-M12
	Weight	23 kg
	Drive	Pneumatisch
Article group code	64075	

Product images