



Pneumatic tapping machine M3~M16 (with 90° adapter)

Description

This pneumatic tapping arm, type AT-16/II+AT16-90° has a working range of up to 1900 mm. The tapping capacity of this machine is M3-M16. As standard, this tapping arm is supplied with reducer, adapter for drilling and 90° adapter for tapping in various directions. Thanks to its construction, the arm can be quickly and easily positioned near the workpiece.

With this tapping arm, internal threads of various sizes can be produced. The design of the movable arm offers you an easy and convenient way of working. Depending on the working conditions, you can also purchase accessories for multifunctional tapping.

Features:

- With reducer, adapter for drilling
- 90° adapter allowing tapping in various directions.
- Supplied with reducer/lubricator set as standard
- Working range between 200 mm and 1900 mm
- For tapping M3-M16
- Including pneumatic tapping spindle With air unit and air hose
- Adapter size: 2
- For professional and industrial use.
- Optional: work table (art. no. 31779)

Including 6 taps with slip clutch

M3 20111812 DIN 371 19/1

M6 20111823 DIN 371 31/2

M8 20111824 DIN 371 31/2

M10 20111826 DIN 371 31/2

M12 20111827 DIN 376 31/2

M16 20111829 DIN 376 31/2

Extra information

Item number	31689	
Model	HU Tap AT-16/II+AT16-90°	
EAN	8718242077590	
CBS Statistics number	84597000	
Article group	HUVEMA Machinery Industry	
Brand	Huvema	
Features	Tap capacity	M3~M16
	Speed	300 rpm
	Working length	200 - 1900 mm
	Tilt up to 90 degrees	yes
	Taps	6 taps with slipping clutch M3-M16
	Weight	27 kg
	Drive	Pneumatisch
Article group code	1667630	

Product images

