



Tapping machine M3~M16

Description

This pneumatic tapping arm type AQ 16-950 has a radius workrange of up to 950 mm and is suitable for tapping M3-M16. Thanks to its design, the arm can be quickly positioned at the workpiece. This tapping arm is used to produce internal threads of various sizes. The arm is easy to mount on a worktop. The design of the movable arm offers you an easy and convenient way to operate. Depending on the working conditions, you can also purchase accessories to enable multi-functional tapping.

Features:

- For tapping M2-M8
- Supplied with reducer/lubricator set as standard
- Workrange between 100 mm and 950 mm
- Pneumatic tapping spindle included
- Column for table mounting
- With air unit and air hose
- For professional and industrial use

Including 6 taps with slipping clutch

M3 20111812 DIN 371 19/1

M6 20111823 DIN 371 31/2

M8 20111824 DIN 371 31/2

M10 20111826 DIN 371 31/2

M12 20111827 DIN 376 31/2

M16 20111829 DIN 376 31/2

Extra information

Item number	31767		
Model	HU Tap AQ-16-950		
EAN	8718242077071		
CBS Statistics number	84597000		
Article group	HUVEMA Machinery Industry		
Brand	Huvema		
Features	Tap capacity	M3~M16	
	Speed	300 rpm	
	Working length	100 - 950 mm	
	Taps	6 taps with slipping clutch M3-M16	
	Weight	24 kg	
	Drive	Pneumatisch	
Article group code	64092		

