



# Tapping machine M3~M16

## Description

This pneumatic tapping arm type AQ 16-950 has a radius workrange of up to 950 mm and is suitable for tapping M3-M16. Thanks to its design, the arm can be quickly positioned at the workpiece. This tapping arm is used to produce internal threads of various sizes. The arm is easy to mount on a worktop. The design of the movable arm offers you an easy and convenient way to operate. Depending on the working conditions, you can also purchase accessories to enable multi-functional tapping.

### Features:

- For tapping M2-M8
- Supplied with reducer/lubricator set as standard
- Workrange between 100 mm and 950 mm
- Pneumatic tapping spindle included
- Column for table mounting
- With air unit and air hose
- For professional and industrial use

Including 6 taps with slipping clutch

M3 20111812 DIN 371 19/1

M6 20111823 DIN 371 31/2

M8 20111824 DIN 371 31/2

M10 20111826 DIN 371 31/2

M12 20111827 DIN 376 31/2

M16 20111829 DIN 376 31/2

## Extra information

---

|                       |                           |                                    |
|-----------------------|---------------------------|------------------------------------|
| Item number           | 31767                     |                                    |
| Model                 | HU Tap AQ-16-950          |                                    |
| EAN                   | 8718242077071             |                                    |
| CBS Statistics number | 84597000                  |                                    |
| Article group         | HUVEMA Machinery Industry |                                    |
| Brand                 | Huvema                    |                                    |
| Features              | Tap capacity              | M3~M16                             |
|                       | Speed                     | 300 rpm                            |
|                       | Working length            | 100 - 950 mm                       |
|                       | Taps                      | 6 taps with slipping clutch M3-M16 |
|                       | Weight                    | 24 kg                              |
|                       | Drive                     | Pneumatisch                        |
| Article group code    | 64092                     |                                    |

