



Lathe machine 460x2000 mm with variable speed and digital readout

Description

The Huvema PROFI series of lathes is an entry-level series of professional lathes from Huvema. Easy to operate, complete in one purchase, solid and affordable, that is what characterizes the Huvema PROFI series. PROFI lathes are the workshop lathes when production is not a necessity.

PROFI lathes are designed with a precision ground and induction hardened bed. The machines have a sturdy base, making them very stable. Operation is very user-friendly, for both small and large sizes. In addition, the machines are supplied complete with 3 claws, 4 claws, travelling, stationary steady, digital readout and cooling. Despite these features, the PROFI series is priced so competitively that it is a match for many workshops, schools and small industries.

Obviously, the PROFI lathes meet the latest CE directives, all to make safe working a standard.

Standard included with this PROFI lathe: 4 jaw chuck 315mm

Newall digital readout

European protective cover

fixed and travelling steady

halogen machine light

solid cast iron base

variable speed

- Self-centering 3-jaw chuck
- Independent 4-jaw chuck
- Adjusting plate
- Stationary steady
- Travelling steady
- Digital readout
- 4-way holder for turning chisels
- Work lamp
- Protective covers
- Cooling system
- Machine maintenance tool set
- Variable speed

Optional for the PROFI lathe:

- Other chucks
- Quick-change chisel holder sets

- Turning centre
- Turning tools
- Drill head

The PROFI lathes are available in various models in terms of size and power range. Can't find a suitable machine in our standard (stock) range? Please feel free to contact us! Our specialists will be happy to help you find the most suitable machine for your application.

Extra information

Item number	30813	
Model	HU 460x2000-4 VAC NG Newall	
EAN	8718242079099	
CBS Statistics number	84581900	
Article group	HUVEMA Machinery Industry	
Brand	Huvema	
Features	Swing over bed	460 mm
	Distance between centres	2000 mm
	Hole through spindle	58 mm
	Engine power	5,5 kW
	Swing over cross slide	270 mm
	Center height	230 mm
	Swing in gap	690 mm
	Width of bed	300 mm
	Number of revs	2
	Speed range	30 - 2000 rpm
	Spindle nose	D1-6 / CAMLOCK
	Taper of main spindle	MT6
	Movement tail stock taper	130 mm
	Tail stock taper	MT4
	Diameter tail stock taper	60 mm
	Cross travel support	285 mm
	Top slide travel	128 mm
	Longitudinal feed	0.031 - 1.7 mm
	Cross feed range	0.014 - 0.784 mm
	Threading metric	0.1 - 14 mm
Threading inch	2 - 112 TPI	
Diameter pitch	4 - 112 DP	
Module pitch	0.1 - 7 MOD	
Voltage	400 V	
Weight	2420 kg	
Machine dimensions	3250 x 1080 x 1370 mm	
Packaging dimensions	3300 x 1130 x 1620 mm	
Article group code	1688934	

Product images

