



Light curtain machine

Description

Robust safety light curtain without dead zone.

Characteristics:

Simple mounting and wiring, varied models for wide application

Perfect self-checking function

Good anti-inference to the surrounding lights and electromagnetic

Good anti-vibration, water-proof and dust-proof performance

Configurated controllers provide double relay contacts output, NPN*2/PNP*2 output can be ordered

LED indicate the running and faults states

Provide double sides protection with S controller

Safety monitoring PNP*2 output, NPN*2 output available (SNC)

Extra information

Item number	40551
Model	SNB0620
EAN	8718242064101
CBS Statistics number	90049012
Article group	K29 - Safety, PPE
Brand	Huvema

Features

Type	LNTECH
Protective range	A series: 0-3000mm;B series:0-8000mm
Protective height	Light axis pitch × (beams-1)
Light ash stitch	20, 40, 80 mm
Detection ability	30, 50, 100 mm
Current	< 200 mA
Feed	DC12V-24V
Charging current	< 200 mA
Protection class	IP65
Operating temperature (min-max)	-10 - 55 °C
Vibration load	Frequency:10-55Hz,Amplitude:0.35m m
Response time	<10 ms
DC	>99 %
MTTFd	120 a
Moisture protection	20°C, RH ≤ 85%
Immunity to light	10000Lux (invalshoek ≥ 5°)
Resistance to impact	15 g, 16 ms, 1000 keer op X-, Y- en Z-as

Article group code

1202140

Product images

