

Huvema Industrial lathes

Huvema's range of European production lathes. Fitted out with variable speed and fully protected. These machines are perfect for all industrial applications. Users are very enthusiastic about these machines!

Also available in:

3 m art.no. 306028 CU 800x3000 VAC

4 m art.no. 306029 CU 800x4000 VAC

5 m art.no. 306030 CU 800x5000 VAC

6 m art.no. 306031 CU 800x6000 VAC

- ▶ variable speed, 3 steps
- ▶ rapid traverse through joystick
- ▶ protective covers
- ▶ halogen machine light
- ▶ cooling system



Specifications

Center height	500mm
Swing over bed	1090mm
Swing over cross slide	690mm
Swing in gap	1250mm
Width of bed	700mm
Distance between centers	1500mm
Spindle taper int./ext.	DIN 55027, gr.15
Hole through spindle	155mm
Spindle speeds	3,7 - 1000 (3)omw/min
Main motor power	30kW
Number of feeds	160
Longitudinal feed range	0,032 - 38,9mm/rev
Cross feed range	0,016 - 19,45mm/rev
Number of thread cuttings	80
Thread cutting metric	0,5 - 480mm
Thread cutting Whitworth	0,0625 - 60TPI
Thread cutting module	0,125 - 120Module
Thread cutting pitch	0,25 - 240DP
Cross slide travel	685mm
Top slide travel	270mm
Tailstock spindle diameter	125mm
Taper tailstock	MT6
Tailstock spindle travel	250mm
Weight	6550kg
Voltage	400V

Options

20121005	SWBH SET D1	Set with quick change base holder and toolholders
322900	Newall DRO-2	Huvema set 2-Axis

Voltage 400V

